

ACCENT SPOT LIGHT

1536SK-3W3K

LED 3W 3000K SPOT LIGHT

The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the user with full control over wattage and color temperature.

| DETAILS | |
|-----------|-------------|
| FINISH: | Satin Black |
| MATERIAL: | Aluminum |
| GLASS: | Clear Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 5.8" |
| HEIGHT: | 3.3" |
| DEPTH: | 2.5 |
| WEIGHT: | 1lb |

| LIGHT SOURCE | |
|---------------------------|-----------|
| LIGHT SOURCE: | LumaCore |
| LED NAME: | 00G3SE-20 |
| VOLTAGE: | 12v |
| VOLT AMPS: | 3.2 |
| COLOR TEMP: | 3000 |
| LUMENS: | 260 |
| CRI: | 80 |
| INCANDESCENT EQUIVALENCY: | 1 x 25w |
| DIMMABLE: | No |
| TRANSFORMER REQUIRED: | Yes |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 18" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 11.5 |
| CARTON WIDTH: | 4.9 |
| CARTON HEIGHT: | 2.8 |
| CARTON WEIGHT: | 1.1 |



PRODUCT DETAILS:

- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- A wiring kit and ground spike are supplied
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optional performance lenses available
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, [click here](#).
- LumaCore Series products carry a lifetime limited warranty