



ARTISTE

900172FBB-LWD

ARTISTE 72" LED SMART FAN

| DETAILS | |
|---------------|-------------|
| FAN FINISH: | Matte Black |
| GLASS: | Etched Opal |
| BLADE COUNT: | 3 |
| SLOPE DEGREE: | 20 |

| DIMENSIONS | |
|------------|-------|
| WIDTH: | 72" |
| HEIGHT: | 15.5" |

| LIGHT SOURCE | |
|--------------|------|
| VOLTAGE: | 120v |

| MOUNTING | |
|------------|---------|
| CANOPY: | 6" Dia. |
| LEAD WIRE: | 1 X 76" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 37.5 |
| CARTON WIDTH: | 16.5 |
| CARTON HEIGHT: | 10 |

Artiste offers a transitional silhouette to enhance any interior or outdoor setting. Elegantly tapered blades are available in a wide array of fashionable finishes to cool and accentuate your space in style. Its integrated warm-dim LED and DC motor technology deliver excellent energy efficiency. Artiste is so versatile; it can be used for both indoor and outdoor spaces.

PRODUCT DETAILS:

- Fan Control included, HIRO Control - 6 Speed Reversing
- For more information on how to control your ceiling fan via the Hinkley Home Automation App, [click here](#).
- This item may be hung on a sloped ceiling
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- WiFi compatible with included fan control
- LED components carry a 5-year limited warranty
- This item includes a 6" down rod. Other various lengths of down rods are available and sold separately to customize the installation height.
- Merging the best of traditional and modern elements with a sophisticated and streamlined look

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com

ARTISTE 72" LED SMART FAN

900172FBB-LWD

| PERFORMANCE SPECIFICATIONS | STANDARD | |
|----------------------------|------------|---------------|
| | HIGH SPEED | AVERAGE SPEED |
| Airflow | 8957 | 6124 |
| EnergyUse | 29.5 | 18 |
| EnergyCost | 8 | 5 |
| Efficiency | 303 | 336 |
| AMPS | 0.4 | 0.23 |
| RPMS | 125 | 85 |