



# WELL LIGHT

55702MZ-LMA30K

HARDY ISLAND LUMACORE 120V

| DETAILS   |              |
|-----------|--------------|
| FINISH:   | Matte Bronze |
| MATERIAL: | Aluminum     |
| GLASS:    | Clear Lens   |
| DIMMABLE: | No           |

| DIMENSIONS |      |
|------------|------|
| WIDTH:     | 4.5" |
| HEIGHT:    | 4"   |
| DEPTH:     | 4.5  |
| WEIGHT:    | 3lb  |

| LIGHT SOURCE              |                                  |
|---------------------------|----------------------------------|
| LIGHT SOURCE:             | Integrated LED                   |
| LED NAME:                 | 30G4SE-120V                      |
| WATTAGE:                  | 12w, 8w, 5w, 3w LED<br>*Included |
| VOLTAGE:                  | 120v                             |
| VOLT AMPS:                | 12.4, 7.8, 5.3, 3.2              |
| LUMENS:                   | 750, 475, 350, 260               |
| CRI:                      | 80                               |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w           |
| DIMMABLE:                 | No                               |

| MOUNTING   |         |
|------------|---------|
| LEAD WIRE: | 1 X 96" |

| SHIPPING       |      |
|----------------|------|
| CARTON LENGTH: | 23.5 |
| CARTON WIDTH:  | 7.5  |
| CARTON HEIGHT: | 5    |
| CARTON WEIGHT: | 2.5  |



## PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- PVC constructed concrete pour kit and burial sleeve are supplied
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- Optimal drive-over protection up to 4,500 lbs
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20°, Spot, 40°, Flood, 60°, Flood

# HINKLEY

HINKLEY  
33000 Pin Oak Parkway  
Avon Lake, OH 44012

PHONE: (440) 653-5500  
Toll Free: 1 (800) 446-5539

[hinkley.com](http://hinkley.com)