



WELL LIGHT

15708MZ-LMA27K

VARIABLE OUTPUT LED 2700K SHIELDED

DETAILS	
FINISH:	Matte Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	5"
DEPTH:	4.5
WEIGHT:	3.4lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	30G4SE-12W
WATTAGE:	12w, 8w, 5w, 3w LumaCore LED *Included
VOLTAGE:	12v
VOLT AMPS:	12.4, 7.8, 5.3, 3.2
LUMENS:	750, 475, 350, 260
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 96"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5

PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Hardy Island Series products carry a lifetime limited warranty
- PVC constructed concrete pour kit and burial sleeve are supplied
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- Three lens options offer versatility in beam spread via an easy to remove and insert assembly - includes: 20° Spot, 40° Flood, 60° Flood

HINKLEY

HINKLEY
33000 Pin Oak Parkway
Avon Lake, OH 44012

PHONE: (440) 653-5500
Toll Free: 1 (800) 446-5539

hinkley.com