

## **PRODUCT DETAILS:**

- Photometrics are based off engine/bulb photometrics at various mounting heights.
- · Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Classic lines and heritage details complement traditional architecture
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.
- LED integrated components carry a 10-year limited warranty

## **BRICK AND DECK**

## 1542BZ-LED

VERTICAL LED DECK SCONCE A wiring kit is supplied.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Frosted
DIMMABLE:	YES, WITH MLV ON TRANSFORMER PRIMARY

DIMENSIONS	
WIDTH:	3.3"
HEIGHT:	4.8"
DEPTH:	2.8

	_
LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	E5050COB
WATTAGE:	1.50w LED *Included
VOLTAGE:	12v
VOLT AMPS:	3.9
LUMENS:	120
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 10w
DIMMABLE:	YES, WITH MLV ON TRANSFORMER PRIMARY
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 16"

SHIPPING	
CARTON LENGTH:	5
CARTON WIDTH:	5
CARTON HEIGHT:	4
CARTON WEIGHT:	1

