

PRODUCT DETAILS:

- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics are based off bulb photometrics.
- Lamp adjustable +/- 20 degrees
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve are supplied
- Includes a dense foam cap to prevent concrete from entering
- Optional Hex Louver lens available (0037HL)
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.

WELL LIGHT

15702BZ

FLAT TOP WELL LIGHT

A wiring kit, PVC constructed concrete pour kit and burial sleeve is supplied. Optional Hex Louver lens available (0037HL). Optimal drive-over protection

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	YES, WITH DIMMABLE LAMP (NOT INCLUDED)

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	3lb

LIGHT SOURCE]
LIGHT SOURCE:	Socketed
WATTAGE:	1-12w MR16 LED, 50w Equiv.
VOLTAGE:	12v
TRANSFORMER REQUIRED:	Yes

МО	UNTING	
LE/	AD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539