







PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Incorporates CREE LEDs with application performance tested by CREE
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
 United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
 Safety Standards
- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Photometrics based off engine photometrics.
- Classic lines and heritage details complement traditional architecture
- Three lens options offer versatility in beam spread via an easy to remove and insert assembly -includes: 20° Spot, 40° Flood, 60° Flood
- For more information on how to control your landscape lighting via the Hinkley Home Automation App, click here.

LUMACORE ACCENT SPOT LIGHT

1536SK-LMA30K

12V VARIABLE OUTPUT LED 3000K SPOT LIGHT

Accentuate your home's architecture and highlight your landscape's natural beauty with a warm ambient glow. Hinkley's Variable Output LumaCORE™ LED Accent Lighting Systems are expertly designed to withstand the elements and provide complete control over wattage and beam spread.

DETAILS	
FINISH:	Satin Black
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	5.8"
HEIGHT:	3.3"
DEPTH:	2.5
WEIGHT:	1lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	30G4SE-12W
WATTAGE:	12w, 8w, 5w, 3w LumaCore LED *Included
VOLTAGE:	12v
VOLT AMPS:	12.4, 7.8, 5.3, 3.2
LUMENS:	750, 475, 350, 260
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	11.5
CARTON WIDTH:	4.9
CARTON HEIGHT:	2.8
CARTON WEIGHT:	1.1



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539